

ShowerTablet Select
Bath thermostat 400 for exposed installation
 Finish: **Brushed Bronze** Article Number: **24340140**



Description

product features

- rotatable bath spout
- 2 functions
- simultaneous utilization of 2 functions
- temperature and volume control
- Select push-button on/off control for 2 outlets
- CoolContact thermostat: Prevents the housing from heating up, making showering even safer
- maximum flow rate at 3 bar: 18,7 l/min
- flow rate for bath spout at 3 bar: 18,7 l/min
- flow rate of hand shower at 3 bar: 15,9 l/min
- min. operating pressure: 1 bar
- max. operating pressure: 10 bar
- safety stop at 40 °C
- temperature limitation adjustable
- with isolated water conduction
- non-return valve
- protected against backflow, according to DIN EN 1717
- with silencer
- suitable for continuous flow water heaters
- material handles: plastic
- shelf made of plastic
- surface shelf: graphite
- connection dimension: DN15
- connection type: s-shaped connections, G ½
- wall-mounted
- centre distance: 150 ± 12 mm
- dirt filter included
- thermostat is delivered with buttons hand shower and bath tub

Technology



Design awards



reddot winner 2021



ShowerTablet Select
Bath thermostat 400 for exposed installation
 Finish: **Brushed Bronze** Article Number: **24340140**



Product image



Scale drawing

