

PRODUCT TECHNICAL SHEET **TECHNICAL DRAWING** 142 Ø 32 VISTA DALL'ALTO Particolare: 158 piattello di fissaggio interno al rosone N° 3 fori x Ø6,3 210 608

PHOTO



PRODUCT FAMILY: HANDBARS AND HANDRAILS - PAINTED SERIES

CODE: 601-I-B DESCRIPTION: Wall mounted grab bar, 600 mm, with right-hand side outrigger. Electrical insulation. White colour.

MECHANICAL PERFORMANCES:

Maximum load 150 kg.

APPROVALS/CERTIFICATIONS:

TUV product certification

TUV system certification UNI EN ISO 9001:2008.

Declaration of Conformity according to European Medical Device Directive 93/42. Reference regulations: Pr EN 1874; UNI EN 12182; UNI CEI EN ISO 14971; UNI EN 1041.

PRODUCT FEATURES:

Ø 32 cold bent body, complete with mounting flanges. The outrigger is brazed to the structure.

The mounting flanges electrically insulate the product.

FIXING/INSTALLATION:

Wall mounting by n° 9 plugs.

Plugs are not included in the package.

Read the instruction sheet to choose the suitable plugs according tho the type of wall.

MAINTENANCE:

Check the correct fastening of the accessories periodically.

Perform a proper cleaning with water and soap, do not use abrasive or corrosive agents or coarse sponges.

PRODUCT COMPOSITION:

N° 1 Pipe Ø32 x 15/10 - DC04 - Zinc-coated and painted RAL9016

N° 3 Mounting flanges Nylon PA6 RAL9016 N° 3 FLange covers Nylon PA6 RAL9016

N° 3 Fixing bushings Brass UNI EN 12164 CW614N

N° 3 Flange fixing screws Steel Tropicalized

TOLERANCES:

GENERAL TOLERANCES - LENGTH (mm) 0÷300 ±3 301÷600 ±4 601÷2000 ±5

PACKAGING OF THE PRODUCT:

Individually wrapped in bubble wrap and packed in cardboard box 670 x 180 x 190 $\,$ mm.

Weight: 2,5 kg

The above mentioned information cannot be considered as binding. Thermomat Saniline Srl

reserves the right to make technical and aesthetic changes without any prior notice.

